

SHURFLO 02

WATER BOOST PUMP TO MAINTAIN WATER PRESSURE

8025 Water Boost Pump: 8025-933-399



APPLICATIONS

Water delivery

FEATURES . BENEFITS

Positive displacement three (3) chamber diaphragm pump
NSF®/UL/CSA-Listed
Self-priming up to 12 ft (3.5 m) vertical
Can run dry without damage
Electric cord
Integrated double check valves

INSTALLATION TIPS

Can mount in any position.
115 Vac nominal with cord.

OPERATION TIPS

Self-priming.

SIZING

Service Flow Rate: 1.6 gpm (6 Lpm)

SHURFLO
8025-933-399

02 



SPECIFICATIONS

Motor

Permanent magnet, P/N 11-195-01, thermally protected

Voltage 115 Vac nominal with cord

Pressure Switch

Adjustable shutoff (80-100 psi (5.51-6.89 bar). Factory set @ 95 psi (6.55 bar) turn on 75 psi \pm 5 psi (5.17 bar \pm 0.34 bar)

Liquid Temperature

180°F (82°C) maximum

Prime

Self-priming up to 12 ft (3.5 m) vertical

Maximum Inlet Pressure 30 psi (2.1 bar)

Cam 3.0 Degree

Service Flow Rate 1.6 gpm (6 Lpm)

Material

Plastics: Nylon

Valves: Food grade Viton

Diaphragm: Santoprene

Fasteners: Zinc plated steel

Weight 5.3 lbs (2.4 kg)

WARRANTY

Limited Pentair® Warranty is valid from the date of manufacture or with proof of purchase:

2088 - One year
Water Boost - One year
Water Pressure Reducer Valve - One year
8000, 8025, 8010, 8075, 8095 - One year

Pentair will provide a copy of the warranty upon request.