SYSTEM DESCRIPTION

The QC7I Triple 4FC water f Itration system features exclusive Fibredyne™II bacteriostatic media that f Iters sediment down to 0.2 micron* and provides chlorine taste & odor reduction at a f owrate of 7.5 gpm for 45,000 gallons. This system is certified under NSF/ANSI Standards 42 and 53.

FEATURES • BENEFITS

- Proprietary Fibredyne II media reduces chlorine taste & odor while providing particulate reduction down to 0.2 micron*
- Fibredyne II media inhibits the growth of bacteria within the filter to guard against media fouling and optimize performance
- Inlet shutoff valve, f ush valve, and pressure gauges simplify service and monitor operating performance
- Quick-change (QC) cartridges make changing cartridges simple and sanitary
- Reduces a range of contaminants to help ensure clearer, fresher water for consistently great-tasting beverages

- Helps protect equipment to help ensure reliable and ef cient operation resulting in reduced maintenance and downtime
- NSF/ANSI Standard 42 certif ed for Bacteriostatic Effects and the reduction of Chlorine Taste & Odor, and Particulate Class I
- NSF /ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means

APPLICATIONS

- Fountain beverages
- Cold beverages

INSTALLATION TIPS

- Choose a mounting location suitable to support the weight of the system while operating.
- Install vertically and allow 21/2 (6.35 cm) clearance below the cartridge for easy removal and replacement.
- Feed water temperature must not exceed 100°F (38°C).
- Do not install where the system could be exposed to freezing temperatures.
- Feed water supply pressure must not exceed 125 psi (non-shock). When pressure exceeds 85 psi, a pressure reducing valve is recommended.
- Flush cartridges by running water through the system for f ve (5) minutes.
- For more details, see the installation, operation, and maintenance guide included with the system.

