



APPLICATIONS

Fountain Beverage

For Most Single-Carbonator Dispensers

Dispensers Using Up To 25 Tanks Of Syrup
or Bag-In-Box Per Month

FEATURES BENEFITS

Improves the taste of fountain beverages
and helps retain the drink's carbonation

Sanitary cartridge replacement is simple,
quick and clean. Internal filter parts are
never exposed to handling
or contamination

Proprietary Micro-Pure® II filtration media
effectively inhibits the growth of bacteria
on the filter media that can decrease the
life of the product

Protects drink system seals, pump,
tubing and small orifices from clogging,
corrosion and abrasive wear

Never use saddle valve for connection.

Use 3/8" water line.

Install vertically with cartridge
hanging down.

Allow 2 1/2" (6.35 cm) clearance below the
cartridge for easy cartridge replacement.

Flush cartridge by running water through
system for five (5) minutes at full flow.

Change cartridges on a regular six (6)
month preventative maintenance program.

Change cartridges when capacity is
reached or when pressure falls below
10 psi (0.7 bar).

Service flow rate must not exceed
1.67 gpm (6.3 Lpm).

Always flush the filter cartridge of the fi

SPECIFICATIONS

Service Flow Rate

Maximum 1.67 gpm (6.3 Lpm)

Rated Capacity

9,000 gallons (35,069 L)

Pressure Requirement

10 – 125 psi (0.7 – 8.6 bar), non-shock

Temperature

35 – 100°F (2 – 38°C)

Overall Dimension

26.69" H x 8.04" W x 5.25" D
(67.8 cm x 20.4 cm x 13.3 cm)

Inlet Connection

3/8"

Outlet Connection

3/8"

Electrical Connection

None required

Shipping Weight

7 lbs (3.1 kgs)

Operating Weight :

8 lbs (3.6 kgs)