

INSTALLATION TIPS

2" (6.35 cm) clearance below the cartridge for easy cartridge replacement.
Flush cartridge by running water through system for five (5) minutes at full flow.

OPERATION TIPS

Change cartridges on a regular six (6) month preventative maintenance program.

Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar).

Service flow rate must not exceed 3.34 gpm (12.6 Lpm).

Always flush the filter cartridge at time of installation and cartridge change.

APPLICATIONS

Fountain Beverage

For Most Single-Carbonator Dispensers

Dispensers Using Up To 50 Tanks Of Syrup or Bag-In-Box Per Month

FEATURES • BENEFITS

Improves the taste of fountain beverages and helps retain the drink's carbonation

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

Proprietary Micro-Pure® II filtration media effectively inhibits the growth of bacteria on the filter media that can decrease the life of the product

Protects drink system seals, pump, tubing and small orifices from clogging, corrosion and abrasive wear

2.6 L

(L)

ents

(bar), non-shock

)

ns

7 x 5.5" D

m x 13.9 c

on

anne

Electr

No



ITA

AIR.COM

4588 TEL • 86 21 4588 4588 FAX • CHINA WATER@PENTAIR.COM E-MAIL

IA, G
1.120.4

All Pentair trademarks
Because we are

of their respective owners
notice.

EV9275-02 MY16