



EVERPURE®

DELIVERS PREMIUM QUALITY WATER FOR FOUNTAIN APPLICATIONS

System: EV9328-02
MC² Replacement Cartridge: EV9612-56
EC210 Prefilter Cartridge: EV9534-26

APPLICATIONS

Fountain
Single-Carbonator Dispensers

Dispensers Using Up To 50 Tanks Of Syrup
or Bag-In-Box Per Month



FEATURES • BENEFITS

Improves the taste of fountain beverages

Reduces chlorine taste & odor and other
offensive contaminants

Manifold features water shut-off, flushing
valve, inlet and outlet pressure gauges

20" prefilter reduces dirt and particles

NSF/ANSI Standard 53 certified to reduce
cysts such as *Cryptosporidium* and *Giardia*
by mechanical means

* Validated by ISO 17025 accredited lab
for 99.999% reduction of *Pseudomonas*
diminuta following the ASTM F838-05
protocol for the validation of 0.2 µm
sterilizing grade filters.

Proprietary Micro-Pure® II filtration media
effectively inhibits the growth of bacteria
on the filter media that can decrease
product life

Exclusive precoat filtration provides
superior chlorine taste & odor reduction
and micro-filters dirt and particles as
small as 0.2* micron in size by
mechanical means

SIZING

Rated Capacity: 18,000 gallons (68,137.4 L)

Service Flow Rate: Maximum 3.34 gpm
(12.6 Lpm)

Choose a mounting location suitable to
support the full weight of the system
when operating.

Never use saddle valve for connection.

Use 3/4" water line.

Install vertically with cartridges
hanging down.

Allow 2½" (6.35 cm) clearance below the
cartridge for easy cartridge replacement.

Flush cartridges by running water through
system for five (5) minutes at full flow.

Change cartridges on a regular six (6)
month preventative maintenance program.

Change cartridges when capacity is
reached or when pressure falls below
10 psi (0.7 bar).

Always flush the filter cartridge at time of
installation and cartridge change.

Inspect Everpure EC210 Cartridge
periodically to determine dirt load.

Replace Everpure EC210 Cartridge when
dirt has penetrated through to the inner
core of the cartridge.

Service Flow Rate

Maximum 3.34 gpm (12.6 Lpm)

Rated Capacity:

18,000 gallons (68,137.4 L)

Pressure Requirements

10–125 psi (0.7–8.6 bar), non-shock

Temperature

35–100°F (2–38°C)

Overall Dimensions

25.59" H x 21.5" W x 6" D
(64.9 cm x 54.6 cm x 15.2 cm)

Inlet Connection



WATER QUALITY SYSTEMS

EVERPURE-SHURFLO WORLD HEADQUARTERS,

EVERPURE-SHURFLO AUSTRALIA,

EVERPURE-SHURFLO CHINA,

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.