



# EVERPURE COLDRINK® 3-MC<sup>2</sup> SYSTEM

DELIVER FOUNTAIN BEVERAGES FOR FOUNTAIN APLICATION

Coldrink 3-MC<sup>2</sup> System: EV9328-03  
MC<sup>2</sup> Replacement Cartridge: EV9612-56  
EC210 Prefilter Cartridge: EV9534-26



## APPLICATIONS

Fountain Beverages  
For Most Dual-Carbonator Dispensers

## FEATURES & BENEFITS

- Improves the taste of fountain beverages and helps retain the drink's carbonation
- Sanitary cartridge replacement is simple, quick and clean; internal filter parts are never exposed to handling or contamination
- Protects drink system seals, pump, tubing and small orifices from clogging, corrosion and abrasive wear
- Proprietary Micro-Pure® II filtration media effectively inhibits the growth of bacteria on the filter media that can decrease product life
- Exclusive precoat filtration provides superior chlorine taste & odor reduction and micro-filters dirt and particles as small as 0.2\* micron in size by mechanical means

- Reduces chlorine taste & odor and other offensive contaminants
- Manifold features water shut-off, flushing valve, inlet and outlet pressure gauges
- 20" prefilter reduces dirt and particles
- NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means

\*

## INSTALLATION

- Choose a mounting location suitable to support the full weight of the system when operating.
- Never use saddle valve for connection.
- Use 3/4" water line.
- Install vertically with cartridges hanging down.
- Allow 2 1/2" (6.35 cm) clearance below the cartridge for easy cartridge replacement.
- Flush cartridges by running water through system for five (5) minutes at full flow.

## OPERATION

- Change cartridges on a regular six (6) month preventative maintenance program.
- Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar).
- Always flush the filter cartridge at time of installation and cartridge change.
- Inspect Everpure EC210 Cartridge periodically to determine dirt load.
- Replace Everpure EC210 Cartridge when dirt has penetrated through to the inner core of the cartridge.

## SPECIFICATIONS

- Service Flow Rate: Maximum 5 gpm (18.9 Lpm)
- Capacity: 27,000 gallons (102,206 L)

FL R  
Maximum 5 gpm (18.9 Lpm)

R C



A ERQ ALI ة ة EM ة

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • FOODSERVICE.PENTAIR.COM  
800.942.1153 (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL  
EVERPURE-SHURFLO AUSTRALIA,

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

© 2016 Pentair Filtration Solutions, LLC. All Rights Reserved.

EV9328-03 DE16