

The **QC7I PF Twin 7FC5-S** water filtration system features exclusive Fibredyne II bacteriostatic media that filters sediment down to 5 microns and provides chlorine taste & odor reduction at a flow rate of 5 gpm for 50,000 gallons. Integrated scale inhibitor media helps protect against scale formation\* on equipment surfaces. The 5 micron mechanical filtration supports lasting, balanced performance with high turbidity water supplies, while an integrated prefilter provides further protection against excessive dirt and sediment. This system is certified under NSF/ANSI Standard 42.

CE á f CE C  
CE á f CE C  
À CE f f 3 -  
F l u s h c a r t  
t h e s y s t e m  
F o r m o r e d  
o p e r a t i o n ,

---

For Pentair Everpure Product Warranties visit:

It is recommended that filter cartridges be replaced every six (6) months on a regular scheduled program, or when capacity is reached or if water pressure or flow to equipment becomes inadequate.

The substances reduced by this drinking water device are not necessarily in your water.

Always replace filter cartridges at least once per year.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.



All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.