


EVERPURE® A







APPLICATIONS








FEATURES • BENEFITS






INSTALLATION TIPS

OPERATION TIPS

SIZING





EVERPURE® A

FV9337-77





Service Flow Rate

M ... 13.36, (50.57 L)

Rated Capacity

96,000 (363,399 L)

Pressure Requirements

10 - 125 , (0.7 - 8.6.), , - i

Temperature Limits

35 - 100 F [2 - 38 C]

Overall Dimensions

36" H 37.5" 13.5" D (91.4 95.2 34.2 34.2

Inlet Connection

3/4" MNP.

Outlet Connection

3/4" MNP.

Shipping Weight

82 . [37.1 i,]

Operating Weight

85 . (38.5 i,)

Electrical Connection

N_H = = .4.

WARRANTY

Everpure water treatment systems by Pentair® (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.



water that may contain filterable cysts.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is

microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected

WATER QUALITY SYSTEMS

ELERP RE H RFLO A . RALIA, 2 A O . 300 576 0 O . . 6 .3 .562.7237 A A **1** -A . A . G A . B A . 7 ELERP RE H RFLO INDIA, B - A E_ERP RE H RFLO E ROPE, A _ A B _ 32 [0] 4 283.505 A A @ 30, B 2200 ELERP RE H RFLO JAPAN INC., A -_A A A A 252 0 43, A A ELERP RE H RFLO O HEA A IA, 3 0 A 65.6768.5800 65.6737.5 4 A