



EVERPURE®

DELIVERS PREMIUM QUALITY WATER FOR FOUNTAIN AND COMBINATION APPLICATIONS

Endurance Twin Cartridge Kit: EV9628-70
Includes 2 - SEN, 1 - 2SR-BW, 1 - Pleated Prefilter

APPLICATIONS

Replacement Cartridge Kit for Everpure Endurance High Flow Twin System

FEATURES • BENEFITS



Reduce chlorine taste & odor and other offensive contaminants that can adversely affect the taste of beverages

Sanitary cartridge replacement is simple, quick and clean; internal filter parts are never exposed to handling or contamination

Protect drink system seals, pump, tubing and small orifices from clogging, corrosion and abrasive wear

Improve the taste of fountain beverages and helps retain the drink's carbonation

Increased capacity for extended reduction of chemical and mechanical contaminants

Balanced cartridge for optimal performance in varying water qualities

Pretreatment provided by unique pleated membrane with a large surface area

Exclusive Fibredyne™ II media provides superior chlorine taste & odor reduction and micro-filters dirt and particles as small as 0.2* micron in size by mechanical means

Utilize Everpure 2SR-BW Phosphate Cartridge for scale reduction†

NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means

INSTALLATION TIPS

Install vertically so cartridge hangs down.

Allow 5" (12.7 cm) clearance below the cartridge for easy cartridge replacement.

Flush cartridge by running water through system for five (5) minutes at full flow.

OPERATION TIPS

Replace cartridge when flow rate becomes inconveniently slow or before rated capacity is reached. It is recommended to replace cartridge at least once per year.

Always flush the filter cartridge at time of installation and cartridge change.

SIZING

Rated Service Flow: 7.5 gpm (28.4 Lpm)

Rated Capacity:
100,000 gallons (378,541 L)

* Validated by ISO 17025 accredited lab for 99.999% reduction of *Pseudomonas diminuta* following the ASTM F838-05 protocol for the validation of 0.2 µm sterilizing grade filters.

† As tested by Pentair.



SPECIFICATIONS

Rated Service Flow

7.5 gpm (28.4 Lpm)

Rated Capacity

100,000 gallons (378,541 L)

Pressure Requirements

10 - 100 psi (0.7 - 6.9 bar), non-shock

Temperature Requirements

35 - 100°F (2 - 38°C)

Shipping Weight

13 lbs (5.89 kgs)

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/or use of our products.

WARRANTY

Everpure water treatment systems by Pentair® (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cat22dg/T2_T10 Tw 6.5 0E p94m) (Since th



WATER QUALITY SYSTEMS

EVERPURE-SHURFLO WORLD HEADQUARTERS,

EVERPURE-SHURFLO AUSTRALIA,

EVERPURE-SHURFLO CHINA,

EVERPURE-SHURFLO INDIA,

EVERPURE-SHURFLO EUROPE,

EVERPURE-SHURFLO JAPAN INC.,

EVERPURE-SHURFLO SOUTHEAST ASIA,

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.