



EVERPURE® HFC-10 SYSTEM

DELIMING EQUIPMENT

HFC-10 Deliming System: EV9100-91



APPLICATIONS

- Commercial Dishwashers
- Commercial Glassware Washers
- Warewashing Booster Heaters

FEATURES • BENEFITS

- Improves equipment efficiency, helps extend the life of equipment and reduces maintenance costs
- Provides simple, efficient deliming of commercial warewashing equipment
- Reduces limescale deposits which can cause equipment failure

- Uses ScaleKleen, Everpure's proprietary food-grade scale remover which is environmentally safe
- System includes; a heavy-duty housing, dip tube assembly, 2.2 lb ScaleKleen™ package and hardness test strip

INSTALLATION TIPS

- System must be installed on inlet water line to equipment.
- Installing a bypass for delimiting is recommended.
- Use 1/2" water line.
- Install vertically using the mounting bracket provided.

OPERATION TIPS

- Follow delimiting schedule as noted in operation manual.
- To determine water hardness and frequency of delimiting, follow instructions on hardness test strip package and compare to hours of operation.

SIZING

Service Flow Rate: Maximum 6 gpm (22.7 Lpm)

Service Flow Rate

Maximum 6 gpm (22.7 Lpm)

Pressure Requirements

10 – 125 psi (0.7 – 8.6 bar), non-shock

Temperature

160°F (94°C)

Overall Dimensions

12.5" L x 5.5" D (31.8 cm x 13.9 cm)

Inlet Connection

1/2"

Outlet Connection

1/2"

Operating Weight**WATER QUALITY SYSTEMS**

EVERPURE-SHURFLO WORLD HEADQUARTERS,