



EVERPURE® ENDURANCE® SC HIGH FLOW TWIN CARTRIDGE KIT

Endurance SC Twin Cartridge Kit: EV9628-80
Includes 2 - SEN, 1 - 2SR-BW

APPLICATIONS

FEATURES • BENEFITS



Balanced cartridge for optimal

†

NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means

of chemical and mechanical

INSTALLATION TIPS

Install vertically so cartridge hangs down.
Allow 5" (12.7 cm) clearance below the cartridge for easy cartridge replacement.
Flush cartridge by running water through system for five (5) minutes at full flow.

OPERATION TIPS

Replace cartridge when flow rate becomes inconveniently slow or before rated capacity is reached. It is recommended to replace cartridge at least once per year.
Always flush the filter cartridge at time of installation and cartridge change.

SIZING

Rated Service Flow: 7.5 gpm (28.4 Lpm)
Rated Capacity:
100,000 gallons (378,541 L)

* Validated by ISO 17025 accredited lab for 99.999% reduction of *Pseudomonas diminuta* following the ASTM F838-05 protocol for the validation of 0.2 µm sterilizing grade filters.

† As tested by Pentair.

EVERPURE® ENDURANCE® SC HIGH FLOW TWIN CARTRIDGE KIT

9628, 80



SPECIFICATIONS

Rated Service Flow

7.5 gpm (28.4 Lpm)

Rated Capacity

100,000 gallons (378,541 L)

Pressure Requirements

10 - 100 psi (0.7 - 6.9 bar), non-shock

Temperature Requirements

35 - 100°F (2 - 38°C)

Shipping Weight

17 lbs. (7.70 kgs.)

WARRANTY