

MRS-225CC-BL REVERSE OSMOSIS SYSTEM SPECIFICATION SHEET



MRS-225CC-BL

Reverse Osmosis System

Capacity: 225 L (852 L)
 Flow Rate: 0.156 L/min (0.591 L/min)
 Filtration: 5-stage
 Filter Type: EverPure
 Filter Life: 6 months

Dimensions: 225 mm (8.9 in) x 156 mm (6.1 in) x 156 mm (6.1 in)
 Weight: 2.25 kg (5.0 lb)
 Installation: Under-sink
 Water Inlet: 1/4" NPT
 Water Outlet: 1/4" NPT
 Drain Outlet: 1/4" NPT
 Power: 120V AC, 15A
 Certification: NSF/ANSI 4, NSF/ANSI 58, NSF/ANSI 61, NSF/ANSI 308

Capacity: 225 L (852 L)

Flow Rate: 0.156 L/min (0.591 L/min)

Capacity: 225 L (852 L)

Flow Rate: 0.156 L/min (0.591 L/min)

Capacity: 225 L (852 L)

Flow Rate: 0.156 L/min (0.591 L/min)

Capacity: 225 L (852 L)

Flow Rate: 0.156 L/min (0.591 L/min)

Capacity: 225 L (852 L)

Flow Rate: 0.156 L/min (0.591 L/min)

EVERPURE® MRS-225CC-BL REVERSE OSMOSIS SYSTEM

9970 19



WARRANTY

EVERPURE warrants the performance of the Reverse Osmosis System for a limited period of time. The warranty is limited to the original purchaser and is non-transferable. The warranty is void if the system is used for commercial purposes, is not installed according to the instructions, or is damaged by misuse, neglect, or accident. For more information, please contact your local EVERPURE distributor or call 1-800-368-3683.

SPECIFICATIONS

Overall Unit Dimensions

38 H 15 (20.5 / i) 8 D
 [965 H 381 (521 / i) 203 D]
 [A 3 (76) i]
 (i i)

Inlet and Outlet Connection

3/8 (9.5) ⌀ D i

Wastewater Line Connection

1/4 (6.4) ⌀ D i

Service Flow Rate

D (i i) i

Minimum Water Supply

1.0 (3.8 L)

Pressure Requirements

⌀ i :
 25 80 i (1.72-5.52), - ⋆
 M i S i :
 100 i (6.89), - ⋆

Inlet Temperature

40 100 F (4 38 C)

Inlet TDS

1,500

Shipping Weight

35 (15.9 ⋆)
 (i i) ⋆