


# BLENDING REVERSE OSMOSIS SYSTEM

System Part Number: EV9975-78



EZ-RO 650/50ATM-BL



EZ-RO 650/50ATM-BL  
four stand bracket



50-gallon atmospheric tank

\*Not performance tested or certified by NSF.

## SYSTEM DESCRIPTION

## FEATURES • BENEFITS

- ◆ Meets NSF 61 and NSF 58 standards; known to significantly reduce lead and copper levels
- ◆ High flow 1/2" ID hose optimized water flow for optimum extraction and taste profile
- ◆ Sealed atmospheric storage tank
- ◆ Built-in bypass, sample port and flush valves speed up installation and maintenance
- ◆ Proprietary Fibredyne™ II filtration media effectively inhibits growth of bacteria on the filter media that can occur over time
- ◆ High efficiency RO membrane saves up to 50% on energy costs

## INSTALLATION TIPS

- ◆ Do not connect to a water line with a water hammer arrestor
- ◆ Do not connect to a water line with a backflow preventer

# EZ-RO™ 650/50ATM-BL BLENDED REVERSE OSMOSIS SYSTEM

EV9975-78

## System

**Overall Dimensions - Processor**  
22.8" H x 18" W x 8.0" D

**Tank Dimensions & Capacity**  
41.3" H x 18.5" W x 25.6" D

### Connections

Inlet: 3/8" push-to-connect  
Outlet: 1/2" OD push-to-connect;  
3/4" garden hose connection

### Pressure Requirements

(3.5– 6.9 bar), non-shock

### Water Temperature

## System

**Shipping Weight**  
86.5 lbs (39.3 kgs)

### Electrical Connection

## Performance

### Daily Production Rate

nominal at 77°F (25°C), 750 ppm NaCl, 60 psi (4.1 bar) feed water

### Service Flow Rate



“ J a u | A' U p | 1'9% l o | U Z % A ; E' | 1' ” “ g' P E A U ” J % E | s Y | o | U k a U x | E a U s i C | f i c Y | U s | x | E a U s i C  
 “ J f E % ' U p | 1' % c | E i E ± ' f a a' p s' | 1' ” “ a Y a U % ” “ d | A | % | o | U k a U x | E a U s i C  
 “ 5 " A a c ' Z A % d K P ' | 1' ” “ % ± ' % ” | China | ” “ d | A | s' % % % U x | E a U s i C  
 1 f a A o % c ! “ a ' 5 A f U d f o | U | ~ | s a U | 1' K i % ” “ d | A | % c % a Y a C | U x | E a U s i C  
 “ Z | E a U q % U | A % C | p | ; E c a Y a U | x % A q | A Y a | d | A f C Y a % ” “ 9 | U E a U | 1 | A % C | 1' ” “ d | A | Y % Y | o | U k a U | a U x | s i C  
 “ C % % ; E s | 1'9% | C f a J K l A ± ' 5 | 1' ” “ 9% | C f a J | U | A a ~ % % C | 1' % Y " 1' ” “ D % % % ” “ 1' C % % ” “ d | A | % f | | o | U k a U | s i A  
 “ 9% A s A | i % ” “ D E ± Y ” | E a U | 1' ” “ ± % d U ” “ ” “ d | A | s Y | o | U k a U x | E a U s i C