

1060DP Series - Pre-Charged (ASME) for Potable Water

JOB: _____	REPRESENTATIVE: _____	
ENGINEER: _____	ORDER NO: _____	DATE _____
CONTRACTOR: _____	SUBMITTED BY: _____	DATE _____
	APPROVED BY: _____	DATE _____

MODEL NO. ORDERED _____	QTY: _____
TAG NO.: _____	
ASME CERTIFICATION REQUIRED <input type="checkbox"/> YES <input type="checkbox"/> NO	
CHARGE PRESSURE: _____ /kPa	
Standard factory charge is 40psi (276kPa) unless otherwise specified.	

- For Domestic Potable Water Systems & Draw down tanks for Pressure Booster Systems.
- Designed and constructed per ASME, Section VIII, Division 1.

MAXIMUM OPERATING CONDITIONS	
Working Temperature	240°F (115°C)
Working Pressure	150psi (1034kPa)

MATERIALS OF CONSTRUCTION	
Shell	Carbon Steel
Liner	Polypropylene
System Connection	Stainless Steel
Fixed Diaphragm	Butyl - FDA approved

Model	Tank Volume	Acceptance Volume	A	B	System Connection NPT	Shipping Weight
	gal. (L)	gal. (L)	in. (mm)	in. (mm)	in. (mm)	lbs. (kg)
1060DP-1	3.5 (13)	2.1 (8.0)	10 (254)	14 (356)	0.75 (19)	22 (10)
1060DP-2	5.0 (19)	3.2 (12.1)	12 (305)	14 (356)	0.75 (19)	28 (12.7)

