

AURORA ACCESSORIES
SUCTION DIFFUSER – MODEL SD

■ Section 1030 Page 203

Dated FEBRUARY 2012

Supersedes Section 1030 Page 203

Dated December 2010

MODEL	Velocity in Feet Per Second (m/s)							
	f/s (m/s)	3 (0.91)	4 (1.22)	5 (1.52)	6 (1.83)	8 (2.44)	10 (3.05)	12 (3.66)
	Pressure Drop in Feet (m) of Water @ Flow in US gpm (l/s)							
SD0215	ft (m) @ Us gpm(l/s)	0.05 (0.02) 19 (1.2)	0.08 (0.02) 25 (1.6)	0.13 (0.04) 32 (2.0)	0.19 (0.06) 38 (2.4)	0.35 (0.11) 52 (3.3)	0.52 (0.16) 63 (4.0)	0.77 (0.23)
		0.11 (0.03) 32 (2.0)	0.20 (0.06) 43 (2.7)	0.32 (0.10) 54 (3.4)	0.43 (0.13) 64 (4.0)	0.80 (0.25) 86 (5.4)	1.28 (0.40) 108 (6.8)	1.72 (0.54) 128 (8.1)
SD2525 SD0325*	ft (m) @ Us gpm(l/s)	0.18 (0.05) 45 (2.8)	0.32 (0.10) 50 (3.2)	0.50 (0.15) 75 (4.7)	0.72 (0.22) 90 (5.7)	1.28 (0.39) 120 (7.6)	2.00 (0.61) 150 (9.5)	2.88 (0.88) 180 (11.4)
SD0303 SD0403*	ft (m) @ Us gpm (l/s)	0.20 (0.06) 70 (4.4)	0.35 (0.11) 92 (5.8)	0.55 (0.17) 115 (7.3)	0.80 (0.24) 138 (8.7)	1.42 (0.43) 185 (11.7)	2.20 (0.67) 230 (14.5)	3.15 (0.96) 276 (17.4)
SD0404 SD0504* SD0604*	ft (m) @ Us gpm(l/s)	0.17 (0.05) 118 (7.4)	0.29 (0.09) 155 (9.8)	0.47 (0.14) 198 (12.5)	0.68 (0.21) 238 (15.0)	1.20 (0.37) 315 (19.9)	1.90 (0.58) 396 (25.0)	2.75 (0.84) 475 (30.0)
SD0505 SD0605*	ft (m) @ Us gpm (l/s)	0.23 (0.07) 187 (11.8)	0.41 (0.13) 250 (15.8)	0.67 (0.20) 315 (19.9)	0.95 (0.29) 375 (23.7)	1.70 (0.52) 500 (31.5)	2.65 (0.81) 625 (39.4)	3.80 (1.16) 750 (47.3)
SD0606 SD0806*	ft (m) @ Us gpm (l/s)	0.22 (0.07) 270 (17.0)	0.38 (0.12) 360 (22.7)	0.60 (0.18) 450 (28.4)	0.86 (0.26) 540 (34.1)	1.54 (0.47) 720 (45.4)	2.40 (0.73) 900 (56.8)	3.45 (1.05) 1080 (68.1)
SD0808 SD1008*	ft (m) @ Us gpm (l/s)	0.21 (0.06) 470 (29.7)	0.37 (0.11) 625 (39.4)	0.58 (0.18) 780 (49.2)	0.85 (0.26) 940 (59.3)	1.50 (0.46) 1250 (78.9)	2.30 (0.70) 1550 (97.8)	3.35 (1.02) 1870 (118.0)
SD1010 SD1210*	ft (m) @ Us gpm (l/s)	0.26 (0.08) 740 (46.7)	0.46 (0.14) 980 (61.8)	0.73 (0.22) 1230 (77.6)	1.03 (0.31) 1480 (93.4)	1.85 (0.56) 1960 (123.7)	2.92 (0.89) 2450 (154.6)	4.20 (1.28) 2940 (185.5)
SD1212 SD1412*	ft (m) @ Us gpm (l/s)	0.25 (0.08) 1080 (68.1)	0.44 (0.13) 1400 (88.3)	0.72 (0.22) 1750 (110.4)	1.02 (0.31) 2100 (132.5)	1.81 (0.55) 2800 (176.7)	2.80 (0.85) 3500 (220.8)	4.00 (1.22) 4200 (265.0)
SD1414 SD1614*	ft (m) @ Us gpm (l/s)	0.28 (0.09) 1440 (90.9)	0.58 (0.18) 1920 (121.1)	0.92 (0.28) 2400 (151.4)	1.23 (0.38) 2880 (181.7)	2.13 (0.65) 3840 (242.3)	3.50 (1.07) 4800 (302.8)	5.30 (1.62) 5760 (363.4)

AURORA ACCESSORIES

■ Section **1030** Page **205**

Dated **FEBRUARY 2012**

10 0 20
2010

AURORA ACCESSORIES
SUCTION DIFFUSER – MODEL SDH

■ Section **1030** Page **207**

Dated **FEBRUARY 2012**

Supersedes Section 1030 Page 207

Dated May 2010

SDH2525 SDH0325*	ft (m) @ Us gpm(l/s)	0.18 (0.05) 45 (2.8)	0.32 (0.10) 50 (3.2)	0.50 (0.15) 75 (4.7)	0.72 (0.22) 90 (5.7)	1.28 (0.39) 120 (7.6)	2.00 (0.61) 150 (9.5)	2.88 (0.88) 180 (11.4)
SDH0404 SDH0504* SDH0604*	ft (m) @ Us gpm(l/s)	0.17 (0.05) 118 (7.4)	0.40 (0.13) 240 (14.7)					
SDH1010 SDH1210*	ft (m) @ Us gpm (l/s)	0.26 (0.08) 740 (46.7)	0.46 (0.14) 980 (61.8)	0.73 (0.22) 1230 (77.6)	1.03 (0.31) 1480 (93.4)	1.85 (0.56) 1960 (123.7)	2.92 (0.89) 2450 (154.6)	4.20 (1.28) 2940 (185.5)

1030 208

MAY 2010

HI PAGE LEF IN EN IONALL BLANK



A vertical line running down the right side of the page, intersecting the two black bars.