

BERKELEY® ECC5 Series

Self-priming centrifugal pump

Volute: Cast iron

Impeller: Polycarbonate

Diffuser: Thermoset

Shaft: One-piece threaded stainless steel

Base: Steel 12 gauge

Maximum Liquid Temperature Limits:
130°F (55°C)

Motor: 1/2 HP, 3450 RPM, 115-volt split phase, 60 Hz. Built-in thermal overload protection with automatic reset.

Mechanical Seal: Buna-N elastomers, carbon and ceramic sealing faces, stainless steel metal part.

Heavy-Duty Ball Bearings: Shielded, permanently lubricated bearings, extensively tested to ensure extended life and smooth, quiet operation.

Built-in Convenience: Comes complete with built-in overload protection with automatic reset and a built-in check valve.

Power Cord: 10', 115 volt.

ORDERING INFORMATION



US: 293 WRIGHT STREET, DELAVAN, WI 53115 WWW.BERKELEYPUMPS.COM PH: 888-782-7483 ORDERS FAX: 800-426-9446
CANADA: 490 PINEBUSH ROAD, UNIT 4, CAMBRIDGE, ONTARIO N1T 0A5 PH: 800-363-7867 ORDERS FAX: 888-606-5484
Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.