

PIPE SIZE	"A" TAP SIZE
2.5" 1823F	1-1/4"
3" 1824F	
4" 1823F	
4" 1824F	
5" 1822F	
5" 1823F	
5" 1824F	
6" 1822F	
6" 1822HHF	
6" 1823HHF	
6" 1823F	
6" 1824F	
6" 1825F	
8" 1822F	
8" 1825F	
8" 1826F	
10" 1823F	
10" 1824DF	
8" 1824F	2"
10" 1824F	
12" 1824F	
ALL VERTICAL (1840) MODELS	3/4"
ALL 2-STAGE (1920) MODELS	1-1/4"
2800/5800 MODELS	3/4"

NOTES:

1. Dimensions are in inches (mm) and may vary  $\pm 1/4"$  (6).
2. Accessories shown are shipped loose for field installation.
3. Casing relief valve is to be adjusted to appropriate pressure upon field installation.
4. Casing relief valve is furnished on electric motor driven units only.
5. Two stage pumps require both vent taps piped to air release valve.
6. Suction gauge range is 30"-0-150 PSI for suction pressures up to 75 PSI, or 30"-0-300 PSI for suction pressures over 75 PSI.
7. Discharge gauge range is 0-300 PSI for pumps with rated discharge pressures up to 150 PSI, or 0-600 PSI for pumps with