

®



Energy Efficient Design

Thermoplastic Sump Pump

High-Output Performance

Thermoplastic construction

Zinc motor housing

Stainless steel fasteners and hardware

Smooth Flow Hydraulics™

Vertical float switch



1/3 HP 3600 GPH
FPZS33V

1/2 HP 4200 GPH
FPZS50V

3/4 HP 4700 GPH
FPZS75V

PERFORMANCE (GPH)							FLOAT SWITCH		SOLIDS HANDLING
DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	15'	20'	MAX. LIFT	ON	OFF	
FPZS33V	3,600	3,060	2,400	1,680	660	22'	7.5'	3'	3/16'
FPZS50V	4,200	3,660	3,000	2,160	960	22'	7.5'	3'	3/16'
FPZS75V	4,700	4,200	3,540	2,820	1,800	24'	7.5'	3'	3/16'

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FPZS33V	1 YEAR	022315368477	8' - 6" x 12.75'	105	7.7 LBS.
FPZS50V	1 YEAR	022315368491	8' - 6" x 12.75'	105	10 LBS
FPZS75V	1 YEAR	022315368507	8' - 6" x 12.75'	105	10 LBS

Included: 1 1/2" NPT discharge, 8' g... e... digg back-... le... ch f...
a... ma... ma... a... r... de... ailed... re... ma... al...
Check Valve placement is recommended

293 W igh, S... ee, Dela a, WI 53115
F... Q... e... r... u... alla... u... r... c... u... r... :
www.flotecwater.com 1-800-365-6832