








1 1/2" / 4 V ) / 4 V ) / 4 V )


HP	VOLTAGE	PHASE	NEC CODE	SF	FULL LOAD AMPS	SF AMPS	LOCKED ROTOR AMPS	RUN KW	START KVA	RUN KVA	MEMO REQ PREMIUM EFFICIENCY @ FL	MTR. EFF. 100% FL	MTR. EFF. 75% FL	MTR. EFF. 50% FL	MTR. EFF. @ SF	PWR. FACT. @ SF	PWR. FACT. 100% FL	PWR. FACT. 75% FL	PWR. FACT. 50% FL
20	208	3	K	1.3	60.2	72.1	402	18.1	160.0	21.6	93	*93	*92	*90	*92	0.85	0.833	0.8	0.74
	230				54.4	65.2	402												
	460				27.2	32.6	201												
	575				21.8	26.1	157												
25	208	3	H	1.3	75.2	88.5	402	23.5	160.0	27.1	93.6	*93.6	*92	*90	*92	0.85	0.854	0.82	0.78
	230				68	80	402												
	460				34	40	201												
	575				27.2	32.0	157												
30	230	3	G	1.3	80.2	96.2	434	26.6	172.7	31.9	93.6	*93.6	*92	*90	*92	0.836	0.856	0.851	0.82
	460				40.1	48.1	217												
	575				32.1	38.5	178												
40	460	3	H	1.3	54.7	63.7	345	34.5	274.6	43.5	94.1	*94.1	*93	*91	*93	0.842	0.842	0.82	0.75
	575				43.8	51.0	265												





















، ا ل ، ا ل ، 8 V )






