

SUBMERSIBLE SOLIDS HANDLING PUMPS

4"
 BALANCED, ENCLOSED, 2 VANE
 35'
 50', 75', 100'

LIQUID HANDLING

	3"
	140°F
	6-9
	0.9-1.1
	28-35 SSU

TEMPERATURE

	311°F
	390°F
	311°F MAX./293°F MIN. 243°F MAX./192°F MIN.

TECHNICAL DATA

	SOOW, W, GGC
	SOOW
	CAST IRON ASTM A-48 CLASS 30
	CAST IRON ASTM A-48 CLASS 30
	DUCTILE IRON ASTM A-536
	BRONZE ASTM B-584-836 ALLOY 115
	416 STAINLESS STEEL
	300 SERIES STAINLESS STEEL
	NITRILE
	UPPER - CARBON/SILICON CARBIDE/FLUROCARBON, TYPE 2100, LOWER - SILICON CARBIDE/CARBON/FLUROCARBON, TYPE 2 UPPER SILICON CARBIDE/SILICON CARBIDE/FLUROCARBON, TYPE 2100 LOWER TUNGSTEN CARBIDE/TUNGSTEN CARBIDE/FLUROCARBON, TYPE 2 LOWER SILICON CARBIDE/SILICON CARBIDE/FLUROCARBON, TYPE 2
	(RADIAL) SINGLE ROW-BALL
	(THRUST) DOUBLE ROW, ANGULAR CONTACT-BALL