



**MYERS®**  
**MODELS 6VC & 6VCX**  
**6" SOLIDS HANDLING**  
**WASTEWATER PUMPS**

**STANDARD (6VC) AND HAZARDOUS LOCATION (6VCX) CONSTRUCTION**



# MYERS® MODEL 6 C & 6 C


## Solids Handling Wastewater Pumps

Product Capabilities		
Capacities To	2400 gpm	151.2 lps
Heads To	146 ft.	44.5 m
Solids Handling	3-3/16 in.	80 mm
Liquids Handling	raw unscreened sewage, effluent, storm water	
Intermittent Liquid Temp.	up to 140°F	

Construction Materials	
Motor Housing, Seal Housing, Cord Cap and Volute Case	cast iron, Class 30, ASTM A48
Enclosed 2-Vane Impeller	ductile iron, Class 65, ASTM A536
Power and Control Cord	SOOW, W
Mechanical Seals:	
Standard	double tandem, type 21 carbon and ceramic
Optional	lower tungsten, carbide
Pump, Motor Shaft	416 SST
Fasteners	300 Series SST
Volute Wear Ring	brass













1101 MYERS PARKWAY  
ASHLAND, OHIO 44805  
PH: 855-274-8948  
WWW.FEMYERS.COM

490 PINEBUSH ROAD, UNIT 4  
CAMBRIDGE, ONTARIO, CANADA N1T 0A5  
PH: 800-387-4386 ORDERS FAX: 888-606-5484  
WWW.FEMYERS.COM

Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.  
K3422 08/07/17 © 2017 Pentair Ltd. All Rights Reserved.