



Submersible Grinder Pumps

WG(X)30H/50H/75H Series



- Dual seal.
- WG(X) packaged for use in Class I, Group D hazardous locations.
- Heads to 170 feet and flows of 98 GPM.
- Recessed impeller provides steep non-overloading operating curve while reducing radial bearing loads and increasing bearing life.
- Oil-filled motor for maximum heat dissipation and constant bearing lubrication.
- High torque capacitor starts single phase or three phase motors for assured starting under heavy load.
- Seal leak probe warns of leak condition, preventing costly motor damage.
- On-winding temperature-sensitive sensor.
- Shredding ring and impeller are replaceable without dismantling pump or motor.

WG(X)75HH/100H/150H Series

- Dual seal.
- WG(X) packaged for use in Class I, Group D hazardous locations.
- Heads to 257 feet and flows of 150 GPM.
- Recessed impeller provides steep non-overloading operating curve while reducing radial bearing loads and increasing bearing life.
- Oil-filled motor for max. heat dissipation and constant bearing lubrication.
- High torque three phase motors for assured starting under heavy load.
- Seal leak probe warns of leak condition, preventing costly motor damage.
- On-winding temperature-sensitive sensor.
- Shredding ring and impeller are replaceable without dismantling pump or motor.

Submersible Grinder Pump Features

A. Sleeve Bearing

- Provides hazardous location integrity

Control Panels

Why you should use Myers Custom Controls

- Quality product, leading in design, construction and engineering
- Quick delivery with virtually unlimited options
- Each control panel is custom built and individually tested
-

Standard Features

- Enclosure with lockable hinged door
- Motor control and alarm circuit breakers
- IEC rated motor starter with adjustable overload relay
- Pump run light (NEMA 4X)
- Hand-off-water selector switch (NEMA 4X)
- Red alarm light (NEMA 4X)
- Motor thermistor/overheat circuit
- Terminal strip
- Schematics laminated to enclosure door
- Terminals to connect off / on / high water floats (Duplex) off / log load / high water floats (Duplex)
- Duplex alternator with load pump selector
- UL 508A listing

Optional Features

- NEMA rated starters
- Motor seal fail and indicator light circuit (required on all dual seal pumps to maintain warranty where applicable)
- Dim glow power indicator flash alarm light
- Alarm test circuit
- Elapsed time meter
- Cycle counters
- Audible alarm silence circuit
- Anti-condensate heater with integral thermostat
- Auxiliary alarm contact
- Lightning arrester
- Alternative level controls
- Variable frequency drives
 - adjustable pump performance
 - liquid level control



740 EAST 9TH STREET,
ASHLAND, OHIO 44805
WWW.FEMYERS.COM

269 TRILLIUM DRIVE, KITCHENER,
ONTARIO, CANADA N2G 4W5
WWW.FEMYERS.COM

Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.
K4393 4/25/14 © 2014 Pentair Ltd. All Rights Reserved.