

SOLIDS HANDLING WASTEWATER PUMPS

3WHV AND V3WHV MODELS

FEATURES

Cable Entry System: Provides double seal protection. Cable jacket sealed by compression fitting. Individual wires sealed by epoxy potting.

Stainless Steel Shaft : Prevents deflection from impeller radial loads when pump operates at heads higher than peak efficiency range.

Single Shaft Seals: Protect motor.

Pump-Out Vanes : Help keep trash from seal, reduce pressure at seal faces.

Horizontal Discharge Volute Case: 3" flanged.

SPECIFICATIONS

Capacities To: 400 GPM (25.24 LPM)

Heads To: 48 ft. (14.6 m)

Solids Handling (dia.): 2-1/2 in. (63.5 mm)

Liquids Handling : Raw unscreened sewage, effluent, storm water

Intermittent Liquid Temp.: Up to 140°F (up to 60°C)

Winding Insulation Temp. (Class B): 266°F (130°C)

Motor Electrical Data: (Single phase motors are capacitor start type. Myers control panels or capacitor kits are recommended for proper operation and warrantcrr6 (r7-19]TJE5)01AA4(r)8

APPLICATIONS

Designed for light and medium commercial applications.

SOLIDS HANDLING WASTEWATER PUMPS 3MW SERIES



All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

©2023 Pentair. All Rights Reserved.

K3239 (08-01-23)