

MYERSC28 20

+ , +* 3 5 (6 6 8 5 (5(& 352 & 7 , 3 * 26 3083

+25 63(2(55(4 80(5167

GPM	RPM	Horsepower Required For:								
		36,	36,	36,	36,	36,	36,	36,	36,	36,

./ 2 \$ 7 35250\$ & \$ \$

LPM	RPM	Kilowatts Required For:								
		% 5	% 5	% 5	% 5	% 5	% 5	% 5	% 5	% 5

2YHU D FHQWXU\ RI H[SHULHQFH KDV SURYHQ WKDW WKH 3HQWDLU V 0\HUV C
 SXPSV DUH GHVLJQHG DQG EXLOW ZLWK SHUIRUPDQFH \RX FDQ UHO\ RQ 2XU
 UHFLSURFDWLQJ SXPS FRPELQHV PDQXIDFWXULQJ H[SHUWLHV DQG DSSOLFD
 D SXPS WKDW LV SHUIHFV IRU D YDULHW\ RI KLJK SUHVXUH MREV)RU GHW
 VDOHV UHSUHVHQWDWLYH RU FXVWRPHU VHU\LFH DW

+RUVHSRZHU UHTXLHG LV EDVHG XS)RUPXG 3HGH*3XLUU . / 3 \$ %

ADVANTAGES BY DESIGN

HANDLES WIDE RANGE OF DEMANDING INDUSTRIAL APPLICATIONS.

+LJK VWUHQJWK I D\GHMQR UDQJW SULQV RRG SXPSDOW\ XS
 WR SVL RI ODUJH ZDWHU YROXPHV 0RWRU 3XPSHYK 3XPS
 3XPSV OLTXLGV WRFHV\ LQ FDOHZD\ OYHJHG SOHDGHU DQG
 RWKHU DSSOLFDWLRQV 12 -RHSRZHU UHTXLUPHQWV IRU DQ LQ
 REWDLQHG E\ PXOWLSO\LQJ WKH ILJXU
 DGYHUWLVHG 3RUVHSRZHU DW RSHUDW

352 887 83% , 7 , (368) , \$ 21,6

Catalog Number	Max. Rated Capacity GPM (LPM)	Max. Rated Pressure PSI (Bar)	Temp. Rating F (C)	Size in inches (mm)						Approx. Wgt. Lbs. (kg)
				& \ O L Q G H U	6 X F W L R O L V F E D H J	3 L V W R O	Q S S K D M W . H Z D \	[[
& 7ULSOH[





740 EAST 9TH STREET, 490 PINEBU