



## SPECIFICATIONS

Application	Sanitary, Emergency, Transfer						
Capacity	130 GPM / 492 LPM						
Stroke	18" / 5.5"						
Options	<table border="1"> <tr> <td>Temperature: 0</td> <td>16</td> <td>406.4</td> </tr> <tr> <td>Temperature: 0</td> <td>7</td> <td>177.8</td> </tr> </table>	Temperature: 0	16	406.4	Temperature: 0	7	177.8
Temperature: 0	16	406.4					
Temperature: 0	7	177.8					
Stroke	2 / 50.8						
Temperature	130 F / 54.4 C						
Motor	1/2 HP, 1550 RPM, 115 V, 230 Hz, 60 Hz, Oil-filled, Ball-bearing						
Application	5-9						
Stroke	T-6AC / C-6AC						
Motor	C-1-1-1						
Stroke	C-1-1-1						
Options	<table border="1"> <tr> <td>Stroke</td> <td>10" / 20"</td> <td>16-3</td> </tr> <tr> <td>Stroke</td> <td>SJT / -A/SJT</td> <td>ii</td> </tr> </table>	Stroke	10" / 20"	16-3	Stroke	SJT / -A/SJT	ii
Stroke	10" / 20"	16-3					
Stroke	SJT / -A/SJT	ii					
Stroke	2						



## FEATURES

Stroke: 2 / Capacity: 130 GPM / Stroke: 18" / Options: Temperature: 0 / Stroke: 2 / Motor: 1/2 HP, 1550 RPM, 115 V, 230 Hz, 60 Hz, Oil-filled, Ball-bearing / Application: 5-9 / Stroke: T-6AC / C-6AC / Motor: C-1-1-1 / Stroke: C-1-1-1 / Options: Stroke: 10" / 20" / 16-3 / Stroke: SJT / -A/SJT / ii / Stroke: 2

## ORDERING INFORMATION

Model	Capacity	Stroke	Options	Temperature	Stroke	Options
MWS550110M	1/2	13.0	115	1/60	10"	Manual - -
MWS550110T					Tethered 16" 7"	
MWS550120M	1/2	13.0	115	1/60	20"	Manual - -
MWS550120T					Tethered 16" 7"	

Noryl® is a registered trademark of General Electric Co. Specifications are subject to change without notice.



SA  
293 RIGHT STREET, DELA. AN. 153115

055 003-11DD T, 0 T 18 NIT64 0 T 118.5640 T 1814 T 0-MBRIDGE T, 0 T 180NT1 0-426

By the undersigned, i... P...  
© 2015 Pentair LLC. All Rights Reserved.