MYERS[®]

33

The Myers SSM33I series pumps are engineered for performance in a variety of demanding drainage applications. The heavy-duty cast iron housing and oil-filled motor maximize heat dissipation for trouble-free operation and years of reliable service. Models available with tethered or vertical switch.

APPLICATIONS

Ba. ,_, ,, d a_ ,, ,

SPECIFICATIONS

Capacities 31 GPM (117 LPM) Shut-off Head 23' (7) Operation: 0, 9.94 (252) 0 4.06 (103) Solids Handling 1/2 (12.7 1 Liquids Handling Da, a, Intermittent Liquid Temperature U _ 140/F (60/C) Motor/Electrical Data 1/3 HP, , ad d , 115V, 9A, 1, , 60H Acceptable pH Range 5-9 Shaft Seal T 11A, ca b a, dc a c Housing H a. ca., **Power Cord** 10' a, d 20', 16/3, SJTW, SJTW-A Discharge, NPT 1-1/2 Min. Sump Diameter 12 (304.8)

FEATURES

Rugged and Reliable

D ab - d _ c _ , b a , b ca, a, d a , a, d, a,

Versatile Performance $D = \frac{1}{1} d d a_{1} d a_{1} a_{1}$ $a_{1} = \frac{1}{1} d a_{1} a_{1}$ $a_{1} = \frac{1}{1} d a_{1} a_{1}$ $a_{1} = \frac{1}{1} d a_{1} a_{1}$ $a_{1} = \frac{1}{1} d a_{1} a_{1}$

Heavy-duty Design

R₁₁₁ d ca. , , , , , a, d , a d , a.d., a, a, d , a, d., , a, , c, d., ,

Choice of Switch Types

A a ab , a, a, _ , d a, a, c*, . . . ca a, _ a, c*

Ease of Flow

Rc, d. , , - , a, a, , d. a, d. , d.

Overload Protection

S, add, ____a_, a___-, a___-, a___-, a____a, a____, a___a, a___a,

Heat Safety

ORDERING INFORMATION


Catalog Number	НР	Volts	Phase/ Cycles	Amps	Discharge Size	Swite Type		Cord Length	Approx. Wt. Lbs.
SSM33IM1C	1/3	115	1/60	9	1-1/2"	Ma	а	20	28
SSM33IP-1	1/3	115	1/60	9	1-1/2	T J /A	*	10'	28
SSM33IPC-1	1/3	115	1/60	9	1-1/2	, A د T	•*	20'	28
SSM33IPV1	1/3	115	1/60	9	1-1/2	V JA	_ *	10'	28
SSM33IPV1C	1/3	115	1/60	9	1-1/2	V JĄ	_ *	20'	28945


0 0

MYERS[®]


33

DIMENSIONS





PUMP PERFORMANCE





A 293 , A A , 53115 . . 490 A , 4, A , A 1 0A5 :888-987-8677 A : 800-426-9446 : 800-363-7867 A : 888-606-5484