MPN Series Shallow Well Jet Pumps are corrosion and abrasion resistant and are ideal for wells with pumping levels of 25' or less. Self-priming after the pump housing is initially filled with water.

Capacities to 18 GPM at 30 PSI. Available in 1/2, 3/4 and 1 HP models. Supplied with the industry standard 30-50 pressure switch setting.

APPLICATIONS

Water systems such as booster pump, marine, poultry, mist sprayers, fountains, and water features.

FEATURES

Quality Construction: Fiberglass-reinforced thermoplastic body provides total corrosion resistance and high resistance to abrasion.

Built-in Jet: Shallow-well jet has corrosion-resistant engineered composite nozzle and venturi.

Impeller: Precision-molded for perfect balance. Ultra-smooth for highest performance and efficiency.

Precision Molded Diffuser: Engineered composite diffuser allows pump to prime faster, handle more air.

Heavy Duty Motor: Stainless steel shaft and dual heavy-duty ball bearings.

Heavy Duty Ball Bearings: Shielded, permanently lubricated bearings, extensively tested to ensure extended life and smooth, quiet operation.

Dual Voltage Capability: 1/2, 3/4 and 1 HP models have dual voltage motors and are shipped at 230 Volt setting.

Professional Quality: Pre-set 30-50 PSI allows for cut-in pressure adjustments.

New Nozzle Clean-out: Easy plug removal and access for ease of service.vice.

Fiberglass-reinforced thermoplastic.

Impeller: Engineered composite.

Base: 10-gauge steel.

Nozzle, Venturi, Diffuser: Engineered composite.

OUTLINE DIMENSIONS