INIODEL DVIN

# High Pressure Reciprocating P

## **Understanding Your Needs**

The Myers BXM series combines manufacturing expertise and understanding of applications to provide a pump with strength and versatility for any demanding high-pressure job.

Contact your Pentair sales respresentative or customer service at 419-289-1144 for more details.

#### Wide Performance Range

JSP OSP 8WSRSVLEDU

#### Rugged design for continuous operation


6 FROQLIHOFSDILVIHISTIRREDE 12 G

(PWORD LUXURESUX SONXUELURLUFDWLRQ 6WHHO V X FDWOLORVORY KD DOOCKOLHWALKEH PSPK YPULSTR PV W H P

#### Whisper Quiet Operation

2 Y HVUSVKLHJIHU HODRODOĐEVQRY KO DO UO JOHR ZI L OROFILOQUJQ G H U

### Dimensionabi Data in mm]



Product Capabilities, Specifications											
					Sizes in inches (mm)						
Catalog	Max. Rate	ed Max. Rate	edΓemp. Ra	tinAgopprox. W			Suction S	z <b>∂</b> ischarge	Size		
Number	Capacity	Pressure	F ( C)	lbs. (kg)	Cylinder B	ore Pisto	n Str <b>blæ</b> T	NPT	Input SI	haft Ke	yway
BXM6-1	8 gpm	1500 psi	140	60	1	1-1 16	1	1/2	1	1/4 x 1/8	,
	30.3 lpm	103.4 ba	r (6)0	(27)2	(25)4	(26.99	(25)4	(12)7	(25)4	(6.35 x 3.1	18)

Note: Consult factory for applications outside of these recommendations.



## Horsepower Requirements

- 1. % R Seel monoblock optional aluminum-bronze.
- 2. 3 L VSW R 1977 METION of the North Street Control of th
- 3. % R Solid one-piece, cast iron crankcase. Acrylic window for oil I
- & UVDICENIM/motive-type ductile iron. Standard is right-hand driv Left-hand drive available.
- 5. 0 D% Q D Ball Qealings for crankshaft.
- 6. Continuous Splash Lubrication.
- 7. & R Q Q LNOTHING IL-Qreingth zinc alloy for durability.
- 8. & URV Milkh-b-De-Golth zinc alloy.
- 9. & \ O LLQQQ-H-Wolina-ceramic.
- 10. 9 DHDWV H PHE 40-pilecte stainless steel for less maintenance.
- 11., Q O'HWYT both sides.
- 12. LVFKD"UNPHboth sides.

BXM											
Э											
I GPN	1 I] RPM										



740 EAST 9TH STREET, ASHLAND, OHIO 44805 WWW.FEMYERS.©M 490 PINEBUSH ROAD, UNIT 4, CAMBRIDGE, ONTARIO N1T 0A5 WWWFEMYERS.©M